

(406)322-1303

NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS)
SECTION I: PRODUCT & MANUFACTURER IDENTIFICATION

PRODUCT IDENTIFIER				
FLAME PROJ	ECTORS, FLAME CANS, (ALL CO	LORS)		
PRODUCT USE;				
THEATRICAL	. PYROTECHNICS AND SPECIA	L EFFECTS. DEVICE WILL	EXPEL	
BURNING P	BURNING PROJECTIONS.			
MANUFACTURERS	MANUFACTURERS NAME;			
DISTRIBUTED BY: NEXT FX, INC. MFG. BY: STAGE FX, INC.				
STREET ADDRESS	STREET ADDRESS; CITY; STATE			
184 MCNA	LEY ROAD	COLUMBUS	MT - USA	
ZIP CODE;	TELEPHONE NUMBER;	EMERGENCY NUMBERS;		
59019	(406)322-1303	DOMESTIC - (800)255-	3924	
		INTER +01 (813)248	3-0585	

SECTION II: HAZARDS IDENTIFICATION

WHMIS CLASSIFCATION/GHS CLASSIFCATION: EXPLOSIVE CLASS 1.4





WARNING

HAZARD STATEMENT: FIRE OR PROJECTION HAZARD

PRECAUTIONARY STATEMENTS:

PREVENTION;

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES/STRAY ELECTRICAL CURRENTS - "NO SMOKING"

RESPONSE;

IN CASE OF FIRE: EVACUATE AREA EXPLOSION RISK IN CASE OF FIRE

DO NOT FIGHT FIRE WHEN FIRE HAS REACHED EXPLOSIVE PRODUCT.

PRODUCT USE:

BURNING PROJECTIONS CAN AND WILL IGNITE COMBUSTIBLE MATERIALS. HEIGHT & RADIAL SAFETY DISTANCES SHOULD BE APPLIED. REFER TO LABEL OR MANUFACTURER FOR APPROPRIATE SAFETY DISTANCES FOR SPECIFIC PRODUCT. "FOR PROFESSIONAL USE ONLY" NOT FOR CONSUMER OR RETAIL SALES.

SALES TO PERSONS UNDER (18) YEARS PROHIBITED.

POTENTIAL ACUTE HEALTH EFFECTS:

DEVICE COULD CAUSE SERIOUS BURN INJURIES IF INCORRECTLY USED.

POTENTIAL CHRONIC HEALTH EFFECTS:

THERE ARE NO CHRONIC AFFECTS FROM HANDLING THIS PRODUCT APPROPRIATELY. SEE APPROPRIATE MSDS FOR COMPONENT INGREDIENTS.

NATIONAL FIRE PROTECTION ASSOCIATION RATINGS;

HEALTH HAZARD - 1 FLAMMABILITY - 3 REACTIVITY - 1 SPECIAL - 0



(406)322-1303

NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS) SECTION III: COMPOSITION/INGREDIENT INFORMATION

HAZARDOUS INGREDIENTS	%	CAS NUMBER
NITROCELLULOSE	*	9004-70-0
BARIUM CHLORATE	*	13477-00-4
STRONTIUM NITRATE	*	10042-76-9
SODIUM NITRATE	*	7631-99-4
BLACK COPPER OXIDE	*	1317-38-0
COPPER CARBONATE	*	12069-69-1
AMMONIUM PERCHLORATE	*	7790-98-9
DOUBLE BASE PROPELLANT	*	

^{*} INGREDIENT PERCENTAGES ARE COMPANY PROPRIETARY.

SECTION IV: FIRST AID MEASURES

ROUTES OF ENTRY;	X SKIN CONTACT	- SKIN ABSORPTION	X EYE CONTACT	X INHALATION	X INGESTION

SKIN CONTACT;

PRODUCT ITSELF DOES NOT HAVE ANY SKIN CONTACT HAZARDS. SERIOUS BURNS COULD TAKE PLACE IF ACCIDENTAL IGNITION. CONTENTS (IF SPILLED) SHOULD BE WASHED IMMEDIATELY FROM EXPOSED AREA WITH PLENTY OF SOAP AND WATER.

EYE CONTACT;

PRODUCT ITSELF DOES NOT HAVE ANY EYE CONTACT HAZARDS. SERIOUS EYE INJURIES COULD RESULT IF ACCIDENTAL IGNITION OCCURS. (IF CONTENTS ARE SPILLED) FLUSH EYES FOR A MINIMUM OF 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION;

PRODUCT ITSELF DOES NOT PRESENT AN INHALATION HAZARD. SMOKE FROM DEVICE FUNCTIONING MAY CAUSE IRRITATION IF USED WITHIN NON-VENTILATED OR SMALL CONFINED SPACES.

INGESTION

PRODUCT ITSELF DOES NOT PRESENT AN INGESTION HAZARD. IF CONTENTS ARE ACCIDENTALLY INGESTED, SEEK MEDICAL ATTENTION AS SOON AS POSSIBLE.

ACUTE HEALTH EFFECTS;

SOME INGREDIENTS ARE CONSIDERED IRRITANTS AND SHOULD BE HANDLED AS SUCH IF EXPOSED.

CHRONIC HEALTH EFFECTS;

THERE ARE NO CHRONIC AFFECTS FROM THE HANDLING OF THIS PRODUCT. ALTHOUGH REPEATED CLOSE PROXIMITY USE (WITHOUT HEARING PROTECTION) COULD CAUSE HEARING LOSS.

SECTION V: FIRE FIGHTING MEASURES & RELATED INFORMATION

FLAMMABILITY;	NFPA RATING;
ALL PYROTECHNICS ARE HIGHLY FLAMMABLE	4 - SEVERE HAZARD



NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS)

GENERAL FIRE HAZARDS;

PYROTECHNIC COMPOSITIONS/DEVICES BURN VIOLENTLY AND ARE SELF-OXIDIZED. FASTER BURNING COMPOSITIONS MAY REACH DETONATION LEVELS DEPENDENT LPON COMPOSITION, PACKAGED CONFIGURATION CONTAINMENT.

MEANS OF EXTINGUISHMENT;

PYROTECHNICS ARE SELF-OXIDIZED AND CANNOT BE EXTINGUISHED WITH NORMAL MEANS. DO NOT FIGHT FIRES INVOLVING THE DEVICES. INCIPIENT FIRES MAY BE FOUGHT. DO NOT USE SUFFOCATION METHODS, CLEAR AREA OF PERSONNEL!

SECTION VI: ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES;

DEVICES MAY BE GENTLY PICKED UP AND RE-PACKAGED IN ORIGINAL PACKAGING OR EQUIVALENT. IN CASE PYROTECHNIC COMPOSITION IS SPILLED: KEEP AWAY FROM ANY POSSIBLE IGNITION SOURCES SUCH AS OPEN FLAMES, NON-RATED ELECTRICAL DEVICES. PREVENT AND POSSIBLE ELECTROSTATIC DISCHARGES (FOR EXAMPLE: DO NOT USE A SYNTHETIC DUSTPAN AND BRUSH).

CLEAN-UP PROCEDURES:

PACKAGED DEVICES CAN BE PICKED UP GENTLY. FOR SPILLED MATERIAL, WHICH MAY BE RELEASED ACCIDENTALLY, FLOOD AREA WITH WATER AND USE CONDUCTIVE OR NATURAL MATERIAL UTENSILS FOR PICK-UP, PLACE INTO A CLOSED CONDUCTIVE CONTAINER FOR DISPOSAL.

SECTION VII: HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT;

ALL PYROTECHNICS SHOULD BE HANDLED WITH CAUTION. AVOID OPEN FLAMES, SMOKING, FRICTION, IMPACT, EXCESSIVE HEAT, ELECTROSTATIC DISCHARGES, RADIO FREQUENCY INTERFERENCE AND MOISTURE, (HUMIDITY). SAFETY INSTRUCTIONS INCLUDED IN PACKAGING. IN SOME UNPACKAGED OR EXPLOSIVE/PYROTECHNIC MATERIALS PACKAGED IN OTHER THEN ORIGINAL PACKAGING MAY HAVE TO BE HANDLED AS A HIGHER HAZARD. I.E. 1.1 OR 1.3 CLASSIFICATION.

STORAGE REQUIREMENTS;

STORE IN A COOL, WELL VENTILATED, AND DRY AREA. DEPENDENT UPON APPLICATION, SEPARATION DISTANCES AND SECURITY MEASURES ARE TO BE COMPLIED WITH. STORAGE COMPATIBILITY SHOULD BE MAINTAINED ACCORDANCE WITH FEDERAL REGULATIONS.

SECTION VIII: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS:	ACGIH TLV = N/A	OSHA PEL = N/A	OTHER = N/A
ENGINEERING CONTROLS;			
DEVICES NEED TO	BE USED IN A VENT	ILATED AREA FOR RI	EMOVAL OF SMOKE.
SOME INGREDIENT	S MAY HAVE EXF	POSURE CONTROLS.	THE FOLLOWING
CHEMICALS HAVE	EXPOSURE LEVELS	LISTED ON SPECIF	IC MSDS, (THESE



(406)322-1303

NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS)

PEL'S ARE ONLY APPLICABLE DURING MANUFACTURING);

AMMONIUM PERCHLORATE

PERSONAL PROTECTIVE EQUIPMENT;

SAFETY GLASSES ARE REQUIRED WHEN HANDLING. PREVENTION OR REDUCTION OF STATIC ELECTRICITY SHOULD BE ACCOMPLISHED BY WEARING ALL COTTON CLOTHING.

SECTION IX: PHYSICAL PROPERTIES

Duveren erare	Door & Appearance;	SPECIFIC GRAVITY;
PHYSICAL STATE;	ŕ	'
Solid	NORMALLY BLACK CAN -	N/A
	No Odor	
ODOR THRESHOLD;	VISCOSITY;	PARTITION COEFFICIENT; (N-
N/A	N/A	OCTONAL/WATER)
		N/A
VAPOR DENSITY; (AIR=1)	VAPOR PRESSURE; (MM/HG)	EVAPORATION RATE;
N/A	N/A	N/A
Boiling Point; (°C)	FREEZING POINT; (°C)	PH;
N/A	N/A	N/A
SOLUBILITY IN WATER;	MELTING POINT;	VOC;
N/A	PYROTECHNICS WILL	N/A
	REACH AUTO-IGNITION	
	TEMPERATURE BEFORE	
	MELTING	
FLASHPOINT;	UPPER FLAMMABLE LIMITS;	LOWER FLAMMABLE LIMITS;
N/A	N/A	N/A
AUTO-IGNITION TEMPERATURE;	SENSITIVITY TO IMPACT;	SENSITIVITY TO ELECTROSTATIC;
Approx 440° C	N/A	ONLY WHEN DEVICE IS
		UN-SHUNTED.

SECTION X: STABILITY & REACTIVITY

Сн	EMICAL STABILITY;		IF Unstable, Under what Conditions;
X	STABLE	UNSTABLE	
INC	OMPATIBILITIES OR CONDITIONS	TO AVOID;	
IG	NITION SOURCES.		
Po	SSIBILITY OF HAZARDOUS REACT	ION;	
VE	RY LOW WHEN DEVICE	IS SHUNTED C	IR SHORT CIRCUITED. LOW POSSIBILITY
WI	HEN UN-SHUNTED.		
RE	ACTIVITY;		
Lc	OSE COMPOSITION IS	VERY REACTIVE	TO SOURCES OF IGNITION.
HA	ZARDOUS DECOMPOSITION;		
D	ECOMPOSITION DOES	NOT OCCUR UN	DER NORMAL CIRCUMSTANCES DURING
SI	ORAGE, TRANSPORT A	AND HANDLING.	UPON FUNCTIONING, THIS DEVICE CAN
PF	ODUCE NITRATES ANI	O OTHER OXIDE	s.

SECTION XI: TOXICOLOGICAL INFORMATION

CARCINOGENICITY - IARC;	CARCINOGENICITY - ACGIH;	
THESE DEVICES MAY CONTAIN KNOWN	THESE DEVICES MAY CONTAIN KNOWN	
OR SUSPECTED CARCINOGENS. THE	OR SUSPECTED CARCINOGENS. THE	
FOLLOWING LIST OF CHEMICALS ARE	FOLLOWING LIST OF CHEMICALS ARE	



NEXT FX, INC. SAFETY DATA SHEET

184 MCNALEY ROAD COLUMBUS, MT 59019 (406)322-1303

FLAME PROJECTORS, (ALL COLORS)

CLASSIFIABLE AND YOU SHOULD	CLASSIFIABLE AND YOU SHOULD			
REFER TO SPECIFIC MSDS FOR	REFER TO SPECIFIC MSDS FOR			
ADDITIONAL INFORMATION;	ADDITIONAL INFORMATION;			
ROUTES OF ENTRY;				
(ONLY SPILLED COMPOSITIONS) INHALA	ATION & INGESTION			
MEASURES OF TOXICITY; (INGREDIENTS ONLY)				
NITROCELLULOSE - (ORAL), LD50 (RA	T) >5 MG/KG			
SODIUM NITRATE - (ORAL), LD50 (RA	г) 1267 мg/кg			
STRONTIUM NITRATE - (ORAL), LD50	(RAT) 1892 MG/KG			
Double Base Propellant - (Composition Ingredients); (Oral-Acute),				
LD50 (RAT) 105MG/KG				
CHRONIC EFFECTS ON HUMANS; (INGREDIENTS ONLY)	ACUTE EFFECTS ON HUMANS; (INGREDIENTS ONLY)			
(SEE INGREDIENT SDS) (SEE INGREDIENT SDS)				
OTHER TOXIC EFFECTS ON HUMANS; (SKIN CORROSION/IRRITATION, EYE DAMAGE/IRRITATION, RESPIRATORY OR				
SKIN SENSITIZER, OR ASPIRATION HAZARDS)				
N/A				
GERM CELL MUTAGENICITY;	REPRODUCTIVE TOXICITY;			
N/A N/A				
STOT - SINGLE EXPOSURE;	STOT - REPEATED EXPOSURE;			
N/A				
SYMPTOMS OF OVEREXPOSURE;				
NO OVEREXPOSURE HAZARDS ASSOCIA	TED WITH THE DEVICE OR PRODUCT.			

SECTION XII: ECOLOGICAL INFORMATION

ECOTOXICITY;	BOD5 & COD;
THE FOLLOWING LIST OF CHEMICALS	NOT AVAILABLE
MAY HAVE ADDITIONAL ECOTOXICITY	
INFORMATION ON THEIR SPECIFIC	
MSDS;	
SODIUM NITRATE	
PRODUCTS OF DEGRADATION;	
POSSIBLY HAZARDOUS SHORT TERM,	, DEGRADATION PRODUCTS ARE NOT
LIKELY.	
TOXICITY OF THE PRODUCTS OF BIODEGRADATION:	
THE PRODUCTS OF DEGRADATION A	RE LESS TOXIC THAN THE PRODUCT
ITSELF.	
OTHER ADVERSE AFFECTS;	
NOT AVAILABLE	
BIDACCUMULATION:	Mobility in Soil;
N/A	N/A

SECTION XIII: DISPOSAL CONSIDERATIONS:

EPA WASTE CODES APPLICABLE;

Unused devices will exhibit the characteristics of reactivity in accordance with 40 CFR. D003 would be applicable if $\underline{\text{devices}}$ are considered waste.



NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS)

WASTE DISPOSAL;

(406)322-1303

WASTES MUST BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. AS STATED ABOVE, UNUSED DEVICE DOES EXHIBIT A RCRA CHARACTERISTIC AS DEPICTED BY 40 CFR AND/OR OTHER INTERNATIONAL REGULATIONS. BEST SUITED FOR INCINERATION AT A LICENSED EXPERIENCED DISPOSAL FACILITY. USED DEVICES MAY BE DISPOSED OF IN STANDARD REFUSE CONTAINER.

SECTION XIV: TRANSPORTATION INFORMATION

DOT CLASSIFICATION & UN IDENTIFICATION;

CLASS 1.4G - UNO431 EXPLOSIVE

PROPER SHIPPING NAME & TECHNICAL NAME;

ARTICLES, PYROTECHNIC

SPECIAL PROVISIONS FOR TRANSPORT;

IN CASE OF AN ACCIDENT, THE ERG SHOULD BE CONSULTED FOR EMERGENCY PROCEDURES. EVACUATION WILL BE NECESSARY IF ACCIDENT HAS INVOLVED MULTIPLE DEVICES IN A FIRE OR THE POTENTIAL FOR A FIRE EXISTS.

SECTION XV: REGULATORY INFORMATION:

FEDERAL & STATE REGULATIONS;

REGULATIONS GOVERNING THE MANUFACTURING, USE AND SALE OF PYROTECHNICS AND/OR CHEMICALS ARE APPLICABLE TO THIS PRODUCT LINE. PLEASE CONTACT YOUR DISTRIBUTOR OR THE MANUFACTURER FOR SPECIFIC REGULATIONS IF YOU HAVE QUESTIONS.

OTHER REGULATIONS;

OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200). EINECS: Some of the compositional ingredients are on the European Inventory of Existing Commercial Chemical Substances. Ingredients may have specific Federal, State or local regulations governing thresholds and handling procedures and only apply to the manufacturing of these items. If one of the ingredients in these devices is Potassium Perchlorate, the state of California requires that this warning be given – "Some products may contain Perchlorates. Special Handling may apply!

SEE <u>www.dtsc.ca.gov/hazardouswaste/perchlorate.</u>"

SECTION XVI: OTHER INFORMATION

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. However, We make no warranty of MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL NEXT FX, INC. OR ITS AFFILIATES BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT,



184 McNaley Road Columbus, MT 59019 (406)322-1303

NEXT FX, INC. SAFETY DATA SHEET

FLAME PROJECTORS, (ALL COLORS)

INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSDEVER ARISING, EVEN IF NEXT FX, INC. Affiliates OR CONSULTANTS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DATE PREPARED;	PREPARED BY;	TELEPHONE NUMBER;
18 SEPT. 2013	DENNIS SLICER	(406)322-1304