

NEXT FX, INC. SAFETY DATA SHEET

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

SECTION I: PRODUCT & MANUFACTURER IDENTIFICATION

PRODUCT IDENTIFIER MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM -(ALL COLORS)

PRODUCT USE;		
THEATRICAL PYROTECHNICS AND SPECIAL EFFECTS. DEVICE WILL EXPEL		
BURNING PROJECTION(S). MAXIMUM ALTITUDE IS DEPENDENT UPON		
CUSTOMER ORDER, WITH A MAXIMUM HEIGHT OF 350-400' FOR LARGER		
PRODUCT.		
MANUFACTURERS NAME;		
DISTRIBUTED BY: NEXT FX, INC.	MFG. BY: STAGE F	TX, INC.
STREET ADDRESS;	CITY;	STATE
184 MCNALEY DOAD	COLUMBUE	

 184 McNALEY ROAD
 COLUMBUS
 MT - USA

 ZIP CODE;
 TELEPHONE NUMBER;
 EMERGENCY NUMBERS;

 59019
 (406)322-1303
 DOMESTIC - (800)255-3924

 INTER. - +01 (813)24>-0585

SECTION II: HAZARDS IDENTIFICATION

WHMIS CLASSIFCATION/GHS CLASSIFCATION: EXPLOSIVE CLASS 1.4		
WARNING		
HAZARD STATEMENT: FIRE OR PROJECTION HAZARD		
PRECAUTIONARY STATEMENTS: (PREVENTION) KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES/STRAY ELECTRICAL CURRENTS - "No Smoking"		
Response; In case of Fire: Evacuate area Explosion Risk in case of fire Do NOT fight fire when fire has reached explosive product.		
PRODUCT USE: BURNING PROJECTIONS CAN AND WILL IGNITE COMBUSTIBLE MATERIALS. ALTITUDE AND RADIAL SAFETY DISTANCES SHOULD BE APPLIED. REFER TO LABEL OR MANUFACTURER FOR APPROPRIATE SAFETY DISTANCES FOR SPECIFIC PRODUCT. "FOR PROFESSIONAL USE ONLY" NOT FOR CONSUMER OR RETAIL SALES. SALES TO PERSONS UNDER (18) YEARS PROHIBITED.		
POTENTIAL ACUTE HEALTH EFFECTS: Device could cause serious Burn injuries if incorrectly used.		
POTENTIAL CHRONIC HEALTH EFFECTS: There are no chronic affects from handling this product appropriately. See appropriate msds for component ingredients.		



NEXT FX, INC. SAFETY DATA SHEET

184 MCNALEY ROAD Columbus, MT 59019 (406)322-1303

> MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

NATIONAL FIRE PROTECTION ASSOCIATION RATINGS; HEALTH HAZARD - 1 FLAMMABILITY - 3 REACTIVITY - 1 SPECIAL - 0

SECTION III: COMPOSITION/INGREDIENT INFORMATION

HAZARDOUS INGREDIENTS	%	CAS NUMBER
POTASSIUM PERCHLORATE	*	7778-74-7
STRONTIUM CARBONATE	*	1633-05-2
SARAN RESIN	*	9011-06-7
RED GUM	*	
DEXTRINE	*	9004-53-9
MAGNESIUM	*	7439-95-4
POTASSIUM DICHROMATE	*	7778-50-9
ΤΙΤΑΝΙUΜ	*	7440-32-6
BLACK COPPER OXIDE	*	1317-38-0
POTASSIUM NITRATE	*	7757-79-1
SULFUR	*	7704-34-9
CHARCOAL	*	7440-44-0
BARIUM NITRATE	*	10022-31-8
ALUMINUM	*	7429-90-5
BORIC ACID	*	10043-35-3
ANTIMONY SULFIDE	*	1345-04-6
BARIUM CARBONATE	*	513-77-9
SODIUM BICARBONATE	*	144-55-8
CALCIUM CARBONATE	*	471-34-1

* INGREDIENT PERCENTAGES ARE COMPANY PROPRIETARY. CHEMICAL INGREDIENT LIST COVERS ALL COLOR & EFFECT VARIANTS, BUT MAY VARY WITH SPECIFIC CUSTOM COLORATION AND/OR EFFECT REQUIREMENTS.

SECTION IV: FIRST AID MEASURES

ROUTES OF ENTRY; X SKIN CONTACT - SKIN ABSORPTION X EYE CONTACT X INHALATION X INGESTION		
SKIN CONTACT;		
PRODUCT ITSELF DOES NOT HAVE ANY SKIN CONTACT HAZARDS. SERIOUS		
BURNS COULD TAKE PLACE IF ACCIDENTAL IGNITION. CONTENTS (IF SPILLED)		
SHOULD BE WASHED IMMEDIATELY FROM EXPOSED AREA WITH PLENTY OF		
SDAP AND WATER.		
EYE CONTACT;		
PRODUCT ITSELF DOES NOT HAVE ANY EYE CONTACT HAZARDS. SERIOUS EYE		
INJURIES COULD RESULT IF ACCIDENTAL IGNITION OCCURS. (IF CONTENTS		
ARE SPILLED) FLUSH EYES FOR A MINIMUM OF 15 MINUTES. IF IRRITATION		
PERSISTS, SEEK MEDICAL ATTENTION.		



NEXT FX, INC. SAFETY DATA SHEET

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

INHALATION;

PRODUCT ITSELF DOES NOT PRESENT AN INHALATION HAZARD. SMOKE FROM DEVICE FUNCTIONING MAY CAUSE IRRITATION IF USED WITHIN NON-VENTILATED OR SMALL CONFINED SPACES.

INGESTION;

PRODUCT ITSELF DOES NOT PRESENT AN INGESTION HAZARD. IF CONTENTS ARE ACCIDENTALLY INGESTED, SEEK MEDICAL ATTENTION AS SOON AS POSSIBLE.

ACUTE HEALTH EFFECTS;

SOME INGREDIENTS ARE CONSIDERED IRRITANTS AND SHOULD BE HANDLED AS SUCH IF EXPOSED. THE FOLLOWING IS A LIST OF THOSE INGREDIENTS; BLACK COPPER OXIDE

BARIUM NITRATE

ALUMINUM

BORIC ACID

CALCIUM CARBONATE

CHRONIC HEALTH EFFECTS;

THERE ARE NO CHRONIC AFFECTS FROM THE HANDLING OF THIS PRODUCT. ALTHOUGH REPEATED CLOSE PROXIMITY USE (WITHOUT HEARING PROTECTION) COULD CAUSE HEARING LOSS.

SECTION V: FIRE FIGHTING MEASURES & RELATED INFORMATION

FLAMMABILITY;	NFPA RATING;
ALL PYROTECHNICS ARE HIGHLY FLAMMABLE	4 – SEVERE HAZARD
GENERAL FIRE HAZARDS;	
Pyrotechnic compositions/Devices burn vio	LENTLY AND ARE SELF-
OXIDIZED. FASTER BURNING COMPOSITIONS MAY RE	ACH DETONATION LEVELS
DEPENDENT UPON COMPOSITION, PACKAGED	CONFIGURATION AND/OR
CONTAINMENT. BURNING PROJECTIONS CAN AND V	VILL IGNITE COMBUSTIBLE
MATERIALS. ALTITUDE AND RADIAL SAFETY DISTANC	ES SHOULD BE APPLIED.
MEANS OF EXTINGUISHMENT;	
PYROTECHNICS ARE SELF-OXIDIZED AND CANNOT	BE EXTINGUISHED WITH
NORMAL MEANS. DO NOT FIGHT FIRES INVOLVING	THE DEVICES. INCIPIENT
FIRES MAY BE FOUGHT. DO NOT USE SUFFOCATION	METHODS, CLEAR AREA OF
PERSONNEL!	

SECTION VI: ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES;

DEVICES MAY BE GENTLY PICKED UP AND RE-PACKAGED IN ORIGINAL PACKAGING OR EQUIVALENT. IN CASE PYROTECHNIC COMPOSITION IS SPILLED: KEEP AWAY FROM ANY POSSIBLE IGNITION SOURCES SUCH AS OPEN FLAMES, SPARKS AND NON-RATED ELECTRICAL DEVICES. PREVENT POSSIBLE ELECTROSTATIC DISCHARGES (FOR EXAMPLE: DO NOT USE A SYNTHETIC DUSTPAN AND BRUSH).



NEXT FX, INC. SAFETY DATA SHEET

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

CLEAN-UP PROCEDURES;

PACKAGED DEVICES CAN BE PICKED UP GENTLY. FOR SPILLED MATERIAL, WHICH MAY BE RELEASED ACCIDENTALLY, FLOOD AREA WITH WATER AND USE CONDUCTIVE OR NATURAL MATERIAL UTENSILS FOR PICK-UP. PLACE INTO A CLOSED CONDUCTIVE CONTAINER FOR DISPOSAL.

SECTION VII: HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT;

ALL PYROTECHNICS SHOULD BE HANDLED WITH CAUTION. AVOID OPEN FLAMES, SMOKING, FRICTION, IMPACT, EXCESSIVE HEAT, ELECTROSTATIC DISCHARGES, RADIO FREQUENCY INTERFERENCE AND MOISTURE. DO NOT AIM OPEN END OF THE DEVICE TOWARDS PERSONNEL OR COMBUSTIBLE MATERIALS. SAFETY INSTRUCTIONS INCLUDED IN PACKAGING. IN SOME CASES, UNPACKAGED OR EXPLOSIVE/PYROTECHNIC MATERIALS PACKAGED IN OTHER THEN ORIGINAL PACKAGING MAY HAVE TO BE HANDLED AS A HIGHER HAZARD. I.E. 1.1 OR 1.3 CLASSIFICATION.

STORAGE REQUIREMENTS;

STORE IN A COOL, WELL VENTILATED, AND DRY AREA. DEPENDENT UPON APPLICATION, SEPARATION DISTANCES AND SECURITY MEASURES ARE TO BE COMPLIED WITH. STORAGE COMPATIBILITY SHOULD BE MAINTAINED IN ACCORDANCE WITH FEDERAL REGULATIONS.

SECTION VIII: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS:	ACGIH TLV = N/A	OSHA PEL = N/A	DTHER = N/A
ENGINEERING CONTROLS;	-		
DEVICES NEED TO	BE USED IN A VENT	ILATED AREA FOR RI	EMOVAL OF SMOKE.
Some ingredients may have exposure controls. Larger devices			
SHOULD ONLY BE USED FOR "OUTDOOR" USE ONLY.			
Personal Protective equipment;			
SAFETY GLASSES	ARE REQUIRED	WHEN HANDLING.	PREVENTION OR
REDUCTION OF STATIC ELECTRICITY SHOULD BE ACCOMPLISHED BY WEARING			
ALL COTTON CLOTH	ling.		

SECTION IX: PHYSICAL PROPERTIES

PHYSICAL STATE;	DDDR & APPEARANCE;	SPECIFIC GRAVITY;
Solid	SOLID TUBES USUALLY	N/A
	BLACK - NO ODOR	
ODOR THRESHOLD;	VISCOSITY;	PARTITION COEFFICIENT; (N-
N/A	N/A	OCTONAL/WATER)
		N/A
VAPOR DENSITY; (AIR=1)	VAPOR PRESSURE; (MM/HG)	EVAPORATION RATE;
N/A	N/A	N/A
BOILING POINT; (°C)	FREEZING POINT; (°C)	PH;
N/A	N/A	N/A



NEXT FX, INC. SAFETY DATA SHEET

184 MCNALEY ROAD Columbus, MT 59019 (406)322-1303

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

SOLUBILITY IN WATER;	MELTING POINT;	VOC;
N/A	PYROTECHNICS WILL REACH	N/A
-	AUTO-IGNITION TEMPERATURE	
	BEFORE MELTING	
FLASHPOINT;	UPPER FLAMMABLE LIMITS;	LOWER FLAMMABLE LIMITS;
N/A	N/A	N/A
AUTO-IGNITION TEMPERATURE;	SENSITIVITY TO IMPACT;	SENSITIVITY TO ELECTROSTATIC;
Approx 440 $^{\circ}$ C	N/A	ONLY WHEN DEVICE IS
		UN-SHUNTED.

SECTION X: STABILITY & REACTIVITY

Сн	EMICAL STABILITY;		IF UNSTABLE, UNDER WHAT CONDITIONS;	
X	STABLE	UNSTABLE		
INC	COMPATIBILITIES OR CONDITIONS	το Ανοιο;		
IG	Ignition Sources			
Po	SSIBILITY OF HAZARDOUS REACT	TION;		
VERY LOW WHEN DEVICE IS SHUNTED OR SHORT CIRCUITED. LOW POSSIBILITY				
WHEN UN-SHUNTED.				
Reactivity;				
LOOSE COMPOSITION IS VERY REACTIVE TO SOURCES OF IGNITION.				
HAZARDOUS DECOMPOSITION;				
DECOMPOSITION DOES NOT OCCUR UNDER NORMAL CIRCUMSTANCES DURING				
STORAGE, TRANSPORT AND HANDLING. UPON FUNCTIONING, THIS DEVICE CAN				
PF	PRODUCE NITRATES AND OTHER OXIDES.			

SECTION XI: TOXICOLOGICAL INFORMATION

CARCINOGENICITY - IARC;	CARCINOGENICITY - ACGIH;		
THESE DEVICES MAY CONTAIN KNOWN	THESE DEVICES MAY CONTAIN KNOWN		
OR SUSPECTED CARCINOGENS. THE	OR SUSPECTED CARCINOGENS. THE		
FOLLOWING LIST OF CHEMICALS ARE	FOLLOWING LIST OF CHEMICALS ARE		
CLASSIFIABLE AND YOU SHOULD	CLASSIFIABLE AND YOU SHOULD		
REFER TO SPECIFIC MSDS FOR	REFER TO SPECIFIC MSDS FOR		
ADDITIONAL INFORMATION;	ADDITIONAL INFORMATION;		
ANTIMONY SULFIDE	BORIC ACID		
POTASSIUM DICHROMATE			
SARAN RESIN			
ROUTES OF ENTRY;			
(ONLY SPILLED COMPOSITIONS) SKIN ABSORPTION, INHALATION &			
INGESTION			
MEASURES OF TOXICITY; (INGREDIENTS ONLY)			
MAGNESIUM - (ORAL), LD50 (RAT) 230 MG/KG			
POTASSIUM DICHROMATE - (ORAL), LD50 (RAT) 25 MG/KG, (DERMAL) LD50			
(RABBIT) 14 MG/KG			
POTASSIUM NITRATE - (ORAL), LD50 (RAT) 3015 MG/KG			
SULFUR - (INHALATION), LC50 (RAT) >9.23 MG/L/4H, (ORAL), LD50 (RAT)			
>3000 mg/kg: (Dermal), LD50 (Rabbit)>2000 mg/kg			
CHARCOAL - (ORAL), LD50 (RAT) >10,000 MG/KG			
BARIUM NITRATE - (ORAL), LD50 (RAT) 355 MG/KG			



NEXT FX, INC. SAFETY DATA SHEET

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS)

BORIC ACID - (INHALATION), LC50 (RAT) >0.16 MG/L/4H: (ORAL), LD50		
(RAT) 2660 MG/KG: (DERMAL), LD50 (RABBIT) >2000 MG/KG		
ANTIMONY SULFIDE - (INHALATION), LC50 (RAT) >5.04 MG/L/4H: (ORAL),		
LD50 (RAT) >2000 MG/KG: (DERMAL), LD50 (RAT) >2000 MG/KG		
BARIUM CARBONATE - (ORAL), LD50 (Rat) 418 мg/kg	
SODIUM BICARBONATE - (ORAL), LD50 (RAT) 4220 MG/KG		
CALCIUM CARBONATE - (ORAL), LD50 (RAT) 6450 MG/KG		
CHRONIC EFFECTS ON HUMANS; (INGREDIENTS ONLY)	ACUTE EFFECTS ON HUMANS; (INGREDIENTS ONLY)	
(SEE INGREDIENT SDS) (SEE INGREDIENT SDS)		
OTHER TOXIC EFFECTS ON HUMANS; (SKIN CORROSION/IRRITATION, EYE DAMAGE/IRRITATION, RESPIRATORY OR		
SKIN SENSITIZER, OR ASPIRATION HAZARDS)		
None Known		
GERM CELL MUTAGENICITY;	REPRODUCTIVE TOXICITY;	
DOES NOT APPLY TO DEVICE DOES NOT APPLY TO DEVICE		
STOT - SINGLE EXPOSURE;	STOT - REPEATED EXPOSURE;	
DOES NOT APPLY TO DEVICE DOES NOT APPLY TO DEVICE		
SYMPTOMS OF OVEREXPOSURE;		

NO OVEREXPOSURE HAZARDS ASSOCIATED WITH THE DEVICE OR PRODUCT.

SECTION XII: ECOLOGICAL INFORMATION

Εσοτοχισιτγ;	BDD5 & CDD;	
THE FOLLOWING LIST OF CHEMICALS	DOES NOT APPLY TO THE DEVICE OR	
MAY HAVE ADDITIONAL ECOTOXICITY	PRODUCT COVERED BY THIS SDS.	
INFORMATION ON THEIR SPECIFIC		
SDS;		
POTASSIUM DICHROMATE		
SULFUR		
BORIC ACID		
BARIUM CARBONATE		
SODIUM BICARBONATE		
PRODUCTS OF DEGRADATION;		
POSSIBLY HAZARDOUS SHORT TERM	, DEGRADATION PRODUCTS ARE NOT	
LIKELY.		
TOXICITY OF THE PRODUCTS OF BIODEGRADATION:		
THE PRODUCTS OF DEGRADATION A	RE LESS TOXIC THAN THE PRODUCT	
ITSELF.		
OTHER ADVERSE AFFECTS;		
None Known		
BIDACCUMULATION:	MOBILITY IN SOIL;	
DOES NOT APPLY TO DEVICE	DOES NOT APPLY TO DEVICE	

SECTION XIII: DISPOSAL CONSIDERATIONS:

EPA WASTE CODES APPLICABLE; UNUSED DEVICES WILL EXHIBIT THE CHARACTERISTICS OF REACTIVITY IN ACCORDANCE WITH 40 CFR. D003 WOULD BE APPLICABLE IF <u>DEVICES</u> ARE CONSIDERED WASTE.



NEXT FX, INC. SAFETY DATA SHEET

184 MCNALEY ROAD Columbus, MT 59019 (406)322-1303

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (All Colors)

WASTE DISPOSAL; WASTES MUST BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. AS STATED ABOVE, UNUSED DEVICE DOES EXHIBIT A RCRA CHARACTERISTIC AS DEPICTED BY 40 CFR AND/OR OTHER INTERNATIONAL REGULATIONS. BEST SUITED FOR INCINERATION AT A LICENSED EXPERIENCED DISPOSAL FACILITY. USED DEVICES MAY BE DISPOSED OF IN STANDARD REFUSE CONTAINER.

SECTION XIV: TRANSPORTATION INFORMATION

DOT CLASSIFICATION & UN IDENTIFICATION; CLASS 1.4G - UN0431 EXPLOSIVE PROPER SHIPPING NAME & TECHNICAL NAME; ARTICLES, PYROTECHNIC

SPECIAL PROVISIONS FOR TRANSPORT;

IN CASE OF AN ACCIDENT, THE ERG SHOULD BE CONSULTED FOR EMERGENCY PROCEDURES. EVACUATION WILL BE NECESSARY IF ACCIDENT HAS INVOLVED MULTIPLE DEVICES IN A FIRE OR THE POTENTIAL FOR A FIRE EXISTS.

SECTION XV: REGULATORY INFORMATION:

FEDERAL & STATE REGULATIONS;

REGULATIONS GOVERNING THE MANUFACTURING, USE AND SALE OF PYROTECHNICS AND/OR CHEMICALS ARE APPLICABLE TO THIS PRODUCT LINE. PLEASE CONTACT YOUR DISTRIBUTOR OR THE MANUFACTURER FOR SPECIFIC REGULATIONS IF YOU HAVE QUESTIONS.

OTHER REGULATIONS;

OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 1910.1200). EINECS: CFR SOME OF COMPOSITIONAL THE INGREDIENTS ARE ON THE EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES. INGREDIENTS MAY HAVE SPECIFIC FEDERAL, STATE OR LOCAL REGULATIONS GOVERNING THRESHOLDS AND HANDLING PROCEDURES AND ONLY APPLY TO THE MANUFACTURING OF THESE ITEMS. IF ONE OF THE INGREDIENTS IN THESE DEVICES IS POTASSIUM PERCHLORATE, THE STATE OF CALIFORNIA REQUIRES THAT THIS WARNING BE GIVEN - "SOME PRODUCTS MAY CONTAIN PERCHLORATES. SPECIAL HANDLING MAY APPLY! SEE WWW.DTSC.CA.GOV/HAZARDOUSWASTE/PERCHLORATE."



NEXT FX, INC. SAFETY DATA SHEET

MINES & COMETS, 19MM, 22MM, 30MM, 45MM (SAM), 50MM, 75MM & 100MM, (ALL COLORS) SECTION XVI: OTHER INFORMATION

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL NEXT FX, INC. OR ITS AFFILIATES BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF NEXT FX, INC. AFFILIATES OR CONSULTANTS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DATE PREPARED;	PREPARED BY;	TELEPHONE NUMBER;
18 SEPT. 2013	DENNIS SLICER	(406)322-1304